

# AT 171

|                  |                                    |
|------------------|------------------------------------|
| <b>TIRE SIZE</b> | <b>30X9 -14</b>                    |
| <b>UM</b>        | US STANDARD                        |
| <b>MACHINERY</b> | ATV / MUD BOGGER TRACTOR / TRACTOR |
| <b>VERSION</b>   | STANDARD                           |
| <b>TL/TT</b>     | TL                                 |
| <b>LI/SS</b>     | 77 A8 ; 53 F                       |



## DIMENSIONS US STANDARD

|                 |          |                |     |
|-----------------|----------|----------------|-----|
| <b>USA CODE</b> | 94056873 | <b>RC (IN)</b> | 0   |
| <b>SW (IN)</b>  | 8.3      | <b>RIM REC</b> | W 7 |
| <b>OD (IN)</b>  | 29.7     | <b>RIM ALT</b> | W 6 |
| <b>SLR (IN)</b> | 0        | <b>PR</b>      | 6   |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b>           | <b>20</b> | <b>15</b> |
|----------------------------|-----------|-----------|
| <b>25 MUD BOGGING</b>      | 908       | -         |
| <b>50 MUD BOGGING</b>      | 454       | -         |
| <b>25 CASUAL TRANSPORT</b> | -         | 740       |
| <b>50 CASUL TRANSPORT</b>  | -         | 375       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.