

AS 509

TIRE SIZE	550/45 - 22.5
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	154 A8/150 B
LI/SS FREE ROLLING	166 A8/162 B



РАЗМЕРЫ IS STANDARD

SW (MM)	540	RIM REC	AG 16.00
OD (MM)	1065	ECE	E11-106R-004545
SLR (MM)	479	PR	20
RC (MM)	3250		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.00	3.50	4.00
10 FR	6270	6860	7420
20 FR	5645	6175	6680
30 FR	5020	5490	5915
40 FR	4480	4900	5300
50 FR	4030	4410	4750
10 DW	4440	4860	5250
20 DW	3995	4370	4725
30 DW	3550	3885	4200
40 DW	3170	3470	3750
50 DW	2855	3125	3350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.