

# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>420/70 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINDIMADORA / MAQUINA PARA RECOLHA DOS FRUTOS / TRATOR PEQUENO / TRATOR / CEIFEIRA
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	130 A8 ; 130 B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94069460	<b>RC (IN)</b>	146.8
<b>SW (IN)</b>	16.5	<b>RIM REC</b>	W 13
<b>OD (IN)</b>	49.1	<b>RIM ALT</b>	W 12 ; W 14 L
<b>SLR (IN)</b>	21.9	<b>ECE</b>	E11-106R-007206

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	2310	2690	3070	3440	3820	4190
25	2310	2690	3070	3440	3820	4190
20	2470	2880	3290	3690	4090	4490
5 LT	3100	3610	4120	4620	5130	5630
5 HT	2470	2880	3290	3690	4090	4490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.