


# RIDEMAX IT 697 (M+S)



<b>TIRE SIZE</b>	<b>540/70 R 24 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 D ; 175 A8

## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94072910	<b>RC (IN)</b>	164.6
<b>SW (IN)</b>	21.1	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	53.9	<b>RIM ALT</b>	DW18 L
<b>SLR (IN)</b>	24.6	<b>ECE</b>	E11-106R-007933

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	52	58	65	73
40	4500	5560	6080	7140	8070	8990	9920	10850	12040	13230
30	4860	6010	6580	7720	8720	9720	10710	11720	13010	14290
25	5180	6390	7000	8220	9280	10350	11410	12480	13840	15210
20	5400	6670	7310	8580	9690	10800	11900	13020	14450	15870

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.