

# FORESTECH

|                     |                      |
|---------------------|----------------------|
| <b>TIRE SIZE</b>    | <b>600/55 - 26.5</b> |
| <b>UM</b>           | US STANDARD          |
| <b>CONSTRUCTION</b> | ⊠ BIAS               |
| <b>MACHINERY</b>    | SKOTARE / SKOTARE    |
| <b>VERSION</b>      | STEEL BELTED         |
| <b>TIRE TYPE</b>    | TL                   |
| <b>LI/SS</b>        | 165 A8 ; 172 A2      |



## DIMENSIONER US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94031238 | <b>RC (IN)</b> | 158.7           |
| <b>SW (IN)</b>  | 24.0     | <b>RIM REC</b> | AG 20.00        |
| <b>OD (IN)</b>  | 52.6     | <b>ECE</b>     | E11-106R-003419 |
| <b>SLR (IN)</b> | 24.3     | <b>PR</b>      | 20              |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>73</b> |
|------------------|-----------|
| 25               | 11350     |
| 20               | 12150     |
| 5                | 13890     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.