


AGRIMAX FORTIS

| | |
|---------------------|--|
| TIRE SIZE | 600/70 R 34 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 160 D ; 163 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94050116 | RC (IN) | 201.1 |
| SW (IN) | 23.3 | RIM REC | DW 18 L |
| OD (IN) | 67.1 | RIM ALT | DW 20 B; W 18 L |
| SLR (IN) | 30.0 | ECE | E4-106R-001401 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|-------|-------|-------|-------|
| 40 | 4760 | 5560 | 6250 | 6940 | 7640 | 8230 | 9130 | 9920 |
| 30 | 5000 | 5840 | 6570 | 7300 | 8020 | 8650 | 9590 | 10420 |
| 25 | 5160 | 6020 | 6780 | 7530 | 8280 | 8930 | 9890 | 10750 |
| 20 | 5480 | 6390 | 7200 | 7990 | 8780 | 9480 | 10500 | 11410 |
| 5 LT | 6380 | 7450 | 8380 | 9310 | 10240 | 11030 | 12230 | 13290 |
| 5 HT | 5480 | 6390 | 7200 | 7990 | 8780 | 9480 | 10500 | 11410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.