

# TR 459

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 400/70 - 20                                  |
| <b>UM</b>           | IS STANDARD                                  |
| <b>CONSTRUCTION</b> |  |
| <b>MACHINERY</b>    | TRACTOR / BACKHOE LOADER /<br>BACKHOE LOADER |
| <b>VERSION</b>      | INDUSTRIAL                                   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 149 A8                                       |



## DIMENSIONS IS STANDARD

|                |                    |                 |                 |
|----------------|--------------------|-----------------|-----------------|
| <b>SW (MM)</b> | 404                | <b>ECE</b>      | E11-106R-005332 |
| <b>OD (MM)</b> | 1090               | <b>TRA CODE</b> | R4              |
| <b>RIM REC</b> | 13                 |                 |                 |
| <b>RIM ALT</b> | 12 SDC; 13 SDC; 14 |                 |                 |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.00</b> |
| 40                | 3250        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.