

AGRIMAX RT 855

TIRE SIZE	250/80 R 18
UM	IS STANDARD
CONSTRUCTION	
MACHINERY	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	125 A8 ; 125 B



DIMENSIONS IS STANDARD

SW (MM)	250	RIM REC	W 8
OD (MM)	835	RIM ALT	W 7 ; W 9
SLR (MM)	375	ECE	E11-106R-006605
RC (MM)	2539	SRI	410

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
50	580	680	780	875	975	1060	1175	1240	1355	1470	1570	1650
40	580	680	780	875	975	1060	1175	1240	1355	1470	1570	1650
30	620	730	835	940	1045	1135	1260	1330	1455	1580	1685	1770
10 LT	780	910	1045	1175	1310	1420	1575	1665	1820	1975	2105	2215
10 HT	620	730	835	940	1045	1135	1260	1330	1455	1580	1685	1770

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.