



IS standard



GROWING TOGETHER

TRAC FARM



PRODUCT DATA SHEET



Bias



Technologies



More Lugs



Extra Deep Tread

Performance



Durability



Self-Cleaning



Traction



High Load Capacity



Cut and Chip Resistance



TRAC FARM

TRAC FARM is a heavy-duty tire specifically designed for tractors in soil tillage and haulage applications. Its deep tread and the special cut-and-chip-resistant compound make the tire suitable for the most difficult operating conditions, ensuring the best return on investment during the entire product life-cycle. TRAC FARM has been designed with more lugs providing extraordinary traction and self-cleaning properties.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 20"	11.2 - 20	W 10	W 9	290	1000	463	2940	STD	8	TT	111 A6
	12.4 - 28	W 11	W 9; W 10	320	1295	602	3890	STD	10	TT	124 A6
Ø 28"	12.4 - 28	W 11	W 9; W 10	320	1295	602	3890	STD	12	TT	125 A6
	13.6 - 28	W 12	W 11	365	1345	625	4034	STD	12	TT	128 A6
	16.9 - 28	W 15 L	W 14 L	440	1435	663	4219	STD	12	TT	143 A6
Ø 30"	18.4 - 30	W 16 L	W 15 L	467	1550	716	4557	STD	12	TT	149 A6
	18.4 - 30	W 16 L	W 15 L	470	1565	716	4557	STD	14	TT	151 A6
	18.4 - 30	W 16 L	W 15 L	470	1565	716	4557	HD	14	TT	151 A6

STD: Standard - HD: Heavy Duty



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference