

AS 504

TIRE SIZE	6.00 - 16
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	83 A8
LI/SS FREE ROLLING	95 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	164	RIM REC	4.00 E
OD (MM)	735	RIM ALT	4.50 E; 4½ K
SLR (MM)	343	ECE	E4-106R-002836
RC (MM)	2190	PR	6

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.80
10 FR	965
25 FR	820
30 FR	775
40 FR	690
10 DW	680
25 DW	575
30 DW	545
40 DW	485

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.