

AGRIMAX RT 855

TIRE SIZE	250/85 R 24
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	109 A8/B



РАЗМЕРЫ IS STANDARD

SW (MM)	251	RIM REC	W 8
OD (MM)	1036	RIM ALT	W 7 ; W 9
SLR (MM)	475	ECE	E4-106R-000638
RC (MM)	3104	SRI	500

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	570	660	755	845	940	1030
40	570	660	755	845	940	1030
30	610	710	810	910	1010	1105
10 LT	765	890	1015	1140	1265	1385
10 HT	610	710	810	910	1010	1105

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.