


AGRIMAX PROHARVEST

VF 620/70 R 26

| | |
|--------------|--|
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BIÇERDÖVER |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| | 173 D |



UNDEFINED IS STANDARD

| | | | |
|----------|------|---------|------------------|
| SW (MM) | 620 | RIM REC | DW 21 B |
| OD (MM) | 1528 | RIM ALT | DW 20 B; DW 23 B |
| SLR (MM) | 670 | ECE | E11-106R-0011721 |
| RC (MM) | 4590 | SRI | 725 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1 | 1.2 | 1.4 | 1.6 | 2 | 2.4 | 2.8 |
|---------------|------|------|------|------|------|------|------|------|------|
| 70 | 2545 | 2960 | 3375 | 3790 | 4200 | 4615 | 5090 | 5385 | 5915 |
| FROM 65 TO 40 | 2795 | 3250 | 3705 | 4160 | 4615 | 5070 | 5590 | 5915 | 6500 |
| 30 | 2855 | 3315 | 3780 | 4245 | 4710 | 5175 | 5705 | 6035 | 6630 |
| 20 | 2910 | 3380 | 3855 | 4330 | 4800 | 5275 | 5815 | 6155 | 6760 |
| 10 | 3075 | 3575 | 4080 | 4580 | 5080 | 5580 | 6150 | 6510 | 7150 |
| *UPTO 30 CYC | 3175 | 3690 | 4210 | 4725 | 5240 | 5760 | 6350 | 6720 | 7380 |
| *UPTO 15 CYC | 3790 | 4405 | 5025 | 5640 | 6260 | 6875 | 7580 | 8020 | 8810 |
| *UPTO 10 CYC | 4155 | 4830 | 5505 | 6180 | 6860 | 7535 | 8305 | 8790 | 9655 |
| 10HT | 2855 | 3315 | 3780 | 4245 | 4710 | 5175 | 5705 | 6035 | 6630 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.