

FLOTATION 648

TIRE SIZE	650/65 - 30.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	162 A8/158 B
LI/SS FREE ROLLING	174 A8/170 B



ABMESSUNGEN US STANDARD

USA-CODE	94006458	RC (IN)	194.3
SW (IN)	26.4	RIM REC	AG 20.00
OD (IN)	65.4	ECE	E11-106R-004558
SLR (IN)	28.0	PR	12

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	23	25
5 FR	19210	19950	20680
10 FR	17290	17960	18610
20 FR	15370	15960	16540
25 FR	13720	14250	14770
30 FR	12360	12830	13230
5 DW	13620	14150	14660
10 DW	12270	12730	13190
20 DW	10900	11320	11730
25 DW	9730	10110	10470
30 DW	8760	9090	9370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.