

AW 729

| | |
|---------------------------|---|
| TIRE SIZE | 480/45 - 17 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 134 A8 |
| LI/SS FREE ROLLING | 146 A8 |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 480 | RIM REC | 16.00 |
| OD (MM) | 866 | ECE | E11-106R-006798 |
| SLR (MM) | 400 | | |
| RC (MM) | 2526 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.20 |
|------------|------|
| 10 FR | 4200 |
| 25 FR | 3570 |
| 30 FR | 3360 |
| 40 FR | 3000 |
| 10 DW | 2970 |
| 25 DW | 2525 |
| 30 DW | 2375 |
| 40 DW | 2120 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.