DATA SHEET

PRINTED ON
23-04-2026

AGRIMAX TURF RT 333

TIRE SIZE	**340/85 R 28**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	TRAUBENERNTEMASCHINE / ERNTEMASCHINE FÜR OBST / KLEINTRAKTOR / TRACTOR / ERNTEMASCHINE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	127 A8 ; 127 B

ABMESSUNGEN IS STANDARD

SW (MM)	370	**RIM REC**	W 12
OD (MM)	1289	**RIM ALT**	W11;DW11;DW12
SLR (MM)	585	**ECE**	E11-106R-0010343
RC (MM)	3874	**SRI**	625

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	965	1120	1280	1435	1595	1750
40	965	1120	1280	1435	1595	1750
30	1035	1200	1370	1540	1710	1875
10 LT	1290	1505	1715	1925	2135	2345
10 HT	1035	1200	1370	1540	1710	1875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..