


# AS 504

<b>TIRE SIZE</b>	<b>6.5/80 - 12</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	80 A8
<b>LI/SS FREE ROLLING</b>	93 A8



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	169	<b>RIM REC</b>	5 J
<b>OD (MM)</b>	608	<b>RIM ALT</b>	5 JA
<b>SLR (MM)</b>	283	<b>ECE</b>	E4-106R-002180
<b>RC (MM)</b>	1836	<b>PR</b>	6

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.60
10 FR	910
25 FR	775
30 FR	730
40 FR	650
10 DW	630
25 DW	535
30 DW	505
40 DW	450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.