

AGRIMAX SIRIO

TIRE SIZE	540/65 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	HIGH SPEED
TIRE TYPE	TL
LI/SS	152 D ; 149 E



РАЗМЕРЫ IS STANDARD

SW (MM)	530	RIM REC	W 16 L
OD (MM)	1566	RIM ALT	W 18
SLR (MM)	721	ECE	E4-106R-000815
RC (MM)	4735	SRI	750

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	1530	1755	2015	2275	2535	2795	3025	3250
65	1670	1920	2205	2485	2770	3055	3305	3550
50	1755	2015	2315	2615	2910	3210	3470	3730
40	1830	2105	2415	2725	3035	3350	3620	3890
25	1980	2275	2615	2950	3285	3625	3920	4210
10	2505	2880	3305	3730	4155	4580	4955	5325

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.