


# AS 504

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>6.00 - 16</b>  |
| <b>UM</b>                 | IS STANDARD   |
| <b>CONSTRUCTION</b>       |  BIAS                    |
| <b>MACHINERY</b>          | LEVANTADOR TELESCÓPICO /<br>REBOQUE PARA OS CAMPOS /<br>IMPLEMENTOS AGRÍCOLAS /<br>LEVANTADOR TELESCÓPICO |
| <b>VERSÃO</b>             | HD  |
| <b>TIRE TYPE</b>          | TT  |
| <b>LI/SS DRIVE WHEEL</b>  | 83 A8   |
| <b>LI/SS FREE ROLLING</b> | 95 A8   |



## DIMENSÕES IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 164  | <b>RIM REC</b> | 4.00 E          |
| <b>OD (MM)</b>  | 735  | <b>RIM ALT</b> | 4.50 E; 4½ K    |
| <b>SLR (MM)</b> | 343  | <b>ECE</b>     | E11-106R-005194 |
| <b>RC (MM)</b>  | 2190 | <b>PR</b>      | 6               |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.80 |
|------------|------|
| 10 FR      | 965  |
| 25 FR      | 820  |
| 30 FR      | 775  |
| 40 FR      | 690  |
| 10 DW      | 680  |
| 25 DW      | 575  |
| 30 DW      | 545  |
| 40 DW      | 485  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.