


# EARTHMAX SR 45

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>18.00 R 33</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | STARRER MULDENKIPPER   |
| <b>VERSION</b>      | STANDARD COMPOUND  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 191 B  |



## ABMESSUNGEN US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA-CODE</b> | 94041138 | <b>RIM REC</b>     | 13.00/2.5 |
| <b>OD (IN)</b>  | 73.6     | <b>TRA CODE</b>    | E4        |
| <b>SLR (IN)</b> | 33.7     | <b>STAR RATING</b> | ★★        |
| <b>RC (IN)</b>  | 220.8    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 73    | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 18700 | 19300 | 19800 | 20400 | 21500 | 22000 | 22700 | 23400 | 24000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.