

AGRIMAX RT 955

TIRE SIZE	230/95 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	133 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94028610	RC (IN)	180.9
SW (IN)	9.0	RIM REC	W 7
OD (IN)	59.3	RIM ALT	W 8
SLR (IN)	28.1	ECE	E4-106R-000772

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64
30	1770	2330	2820	3100	3270	3590	3910	4230	4530	-
25	1770	2330	2820	3100	3270	3590	3910	4230	4530	-
20	1900	2480	3020	3310	3510	3850	4190	4530	4860	-
5	2120	2670	3270	3890	4500	4640	5180	5730	6270	6810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.