

# SNOW - RIDE (B)

|                     |                      |
|---------------------|----------------------|
| <b>TIRE SIZE</b>    | 14 - 17.5            |
| <b>UM</b>           | IS STANDARD          |
| <b>CONSTRUCTION</b> | BIAS                 |
| <b>MACHINERY</b>    | BULLDOZER / CHARGEUR |
| <b>VERSION</b>      | STANDARD             |
| <b>TIRE TYPE</b>    | TL                   |
| <b>LI/SS</b>        | 155 A2               |



## DIMENSIONS IS STANDARD

|                 |     |                    |                  |
|-----------------|-----|--------------------|------------------|
| <b>SW (MM)</b>  | 354 | <b>RIM REC</b>     | 10.50            |
| <b>OD (MM)</b>  | 920 | <b>ECE</b>         | E11-106R-0011791 |
| <b>SLR (MM)</b> | 0   | <b>PR</b>          | 14               |
| <b>RC (MM)</b>  | 0   | <b>STAR RATING</b> | 0                |

## LOAD CAPACITY (KG/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>50</b> |
| 5                | 8550      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.