


AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 380/70 R 28 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 127 D |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CODICE USA | 94063055 | RC (IN) | 152.9 |
| SW (IN) | 15.0 | RIM REC | W 12 |
| OD (IN) | 50.9 | RIM ALT | W 11; W 13 |
| SLR (IN) | 23.1 | ECE | E11-106R-005829 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 40 | 2130 | 2470 | 2820 | 3160 | 3520 | 3860 |
| 30 | 2240 | 2600 | 2970 | 3330 | 3690 | 4060 |
| 25 | 2340 | 2710 | 3100 | 3470 | 3860 | 4230 |
| 20 | 2450 | 2840 | 3250 | 3650 | 4050 | 4440 |
| 5 LT | 2840 | 3320 | 3780 | 4240 | 4710 | 5170 |
| 5 HT | 2450 | 2840 | 3250 | 3650 | 4050 | 4440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.