

# AGRIMAX RT 657

|                  |                                          |
|------------------|------------------------------------------|
| <b>TIRE SIZE</b> | <b>420/65 R 30</b>                       |
| <b>UM</b>        | US STANDARD                              |
| <b>MACHINERY</b> | VINEYARD HARVESTER / TRACTOR / HARVESTER |
| <b>VERSION</b>   | STANDARD                                 |
| <b>TL/TT</b>     | TL                                       |
| <b>LI/SS</b>     | 136 D ; 139 A8                           |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94052899 | <b>RC (IN)</b> | 155.6           |
| <b>SW (IN)</b>  | 16.5     | <b>RIM REC</b> | W 13            |
| <b>OD (IN)</b>  | 51.5     | <b>RIM ALT</b> | W 12 ; W 11     |
| <b>SLR (IN)</b> | 23.9     | <b>ECE</b>     | E11-106R-002975 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-------------|------|------|------|------|------|------|------|------|
| <b>40</b>   | 2330 | 2670 | 3060 | 3460 | 3860 | 4250 | 4600 | 4940 |
| <b>30</b>   | 2450 | 2810 | 3230 | 3640 | 4060 | 4480 | 4840 | 5190 |
| <b>25</b>   | 2520 | 2900 | 3330 | 3760 | 4190 | 4610 | 4980 | 5360 |
| <b>20</b>   | 2680 | 3080 | 3530 | 3990 | 4440 | 4890 | 5290 | 5690 |
| <b>5 LT</b> | 3120 | 3580 | 4110 | 4640 | 5170 | 5700 | 6160 | 6620 |
| <b>5 HT</b> | 2680 | 3080 | 3530 | 3990 | 4440 | 4890 | 5290 | 5690 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.