


# AT 171

<b>TIRE SIZE</b>	<b>35X10 - 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	VEÍCULO ATV / VEICULO PARA LAS CORRIDAS DE LAMA / TRATOR
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS</b>	90 A8 ; 66 F



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94053780	<b>RC (IN)</b>	104.2
<b>SW (IN)</b>	9.5	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	35.4	<b>PR</b>	8
<b>SLR (IN)</b>	16.4	<b>TRA CODE</b>	R1W+

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>20</b>	<b>15</b>
<b>25 MUD BOGGING</b>	1325	-
<b>50 MUD BOGGING</b>	665	-
<b>25 CASUAL TRANSPORT</b>	-	1080
<b>50 CASUL TRANSPORT</b>	-	540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.