


AGRIMAX SPARGO

TIRE SIZE	VF 750/60 R 46
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР-ТЯГАЧ
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	189 D



РАЗМЕРЫ IS STANDARD

SW (MM)	755	RIM REC	DW27B
OD (MM)	2086	ECE	E11-106R-009075
SLR (MM)	940	SRI	1000
RC (MM)	6337	TRA CODE	R1

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
70	5525	6100	6765	7145	7525	7815	8100	8480	8860	9195	9525
FROM 65 TO 40	5975	6595	7315	7725	8140	8450	8755	9170	9580	9940	10300
30	6100	6730	7465	7885	8305	8620	8935	9355	9775	10145	10510
20	6215	6860	7610	8040	8465	8790	9110	9540	9965	10340	10715
10	6575	7255	8045	8500	8955	9295	9635	10085	10540	10935	11330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.