

# FLOTATION 558

<b>TIRE SIZE</b>	<b>500/45 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	PRESSE À PAILLE / MOISSONNEUSE / VÉHICULE CITERNE / REMORQUE / MOISSONNEUSE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	136 A8/132 B
<b>LI/SS FREE ROLLING</b>	148 A8/144 B



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94006267	<b>RC (IN)</b>	124.7
<b>SW (IN)</b>	19.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	41.1	<b>ECE</b>	E4-106R-002307
<b>SLR (IN)</b>	18.5	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	33	36	39
<b>5 FR</b>	8860	9290	9720
<b>10 FR</b>	7970	8370	8750
<b>20 FR</b>	7090	7430	7780
<b>25 FR</b>	6330	6640	6940
<b>30 FR</b>	5700	5970	6170
<b>5 DW</b>	6290	6600	6910
<b>10 DW</b>	5670	5940	6220
<b>20 DW</b>	5040	5280	5530
<b>25 DW</b>	4500	4720	4940
<b>30 DW</b>	4050	4240	4410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.