



## LG 306

### Description

LG 306 is a lawn and garden tyre suitable for mowers. In some sizes, LG 306 is also fit for small tractors. The specific tread pattern makes the tyre gentle on the ground, easing handling at the same time. LG 306 is available in an "aramidbelted" version for users who need strengthened puncture resistance.

### UM

US Standard

### Construction

◆ Bias

### Machinery

Agriculture ■ Mower



Version

STANDARD

Tyre Type

TL

Tyre size

20x8.00-10

LI/SS

## Dimensions US Standard

USA Code	94012725
SW (in)	8.1
OD (in)	19.7
SLR (in)	8.8
RC (in)	57.1
Rim Rec	6.00 I - 55; I - 70; I - 90
Rim Alt	6 JA
ECE	E11-106R-003454

## Load Capacity (US)

mph / psi	24
10	910

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..