



## AGRIMAX RT 600



### Description

AGRIMAX RT 600 is the ideal tire for grassland, harvesting and spreading applications. Thanks to its large contact area, AGRIMAX RT 600 ensures an excellent pressure distribution on the land reducing damage on grassland and protecting your soil. Thanks to its round shoulder technology, the reinforced bead and increased number of lugs, it guarantees great stability and traction.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Harvester

Version STANDARD

Tire Type TL

Tyre size 800/65R32

LI/SS 172;D

## Dimensions IS Standard

SW (IS) (mm)	775
OD (IS) (mm)	1820
Rim Rec	DW 27 B
Rim Alt	DH 27 B; DW 25 B
ECE	E11-106R-0010409

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2965	3465	3970	4410	4855	5230	5860	6300
50	3110	3640	4170	4635	5095	5495	6155	6615
40	3245	3795	4350	4830	5315	5730	6420	6900
30	3410	3985	4565	5075	5580	6015	6740	7245
10 LT	3970	4645	5325	5915	6505	7010	7855	8445
10 HT	3410	3985	4565	5075	5580	6015	6740	7245

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..