



BK 6060

Description

BK 6060 is a both field- and road-oriented tire for trailers and backhoe loaders in transport as well as digging and loading applications. This block pattern tire provides an extended tire life-cycle.

UM

IS Standard

Construction

 Bias

Machinery

Industrial & Construction ■ Backhoe Loader



Version	STANDARD
Tire Type	TT
Tyre size	9.00-16
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	255
OD (IS) (mm)	925
SLR (IS) (mm)	427
RC (IS) (mm)	2740
Rim Rec	6.50 H
Rim Alt	6.00 G

Load Capacity (IS)

km/h / bar	7.25
30	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..