



IS standard



GROWING TOGETHER

# EM 936 SUPER



PRODUCT DATA SHEET



Bias



Performance



Comfort



Heavy Duty



Stability



Traction



# EM 936 SUPER

EM 936 SUPER has been specifically designed for excavators and telehandlers in digging and loading operations as well as transport applications. With increased tread width by 8-10%, EM 936 SUPER offers outstanding stability and enhanced riding comfort. It also ensures a high level of handling comfort and provides excellent traction even under heavy-duty service conditions.

|       | Tire size  | Type | PR | LI/SS | Version | S.W.<br>(mm) | O.D.<br>(mm) | SLR<br>(mm) | RC<br>(mm) | RIM  |           |
|-------|------------|------|----|-------|---------|--------------|--------------|-------------|------------|------|-----------|
|       |            |      |    |       |         |              |              |             |            | Rec. | Alt.      |
| Ø 20" | 10.00 - 20 | TT   | 14 | 145 B | STD     | 277          | 1080         | 500         | 3336       | 7.5  | 7.0 ; 8.0 |
|       | 10.00 - 20 | TT   | 16 | 146 B | STD     | 277          | 1080         | 500         | 3336       | 7.5  | 7.0 ; 8.0 |

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference