



PL 801

Description

PL 801 has been specially designed for hay harvesting applications with rotor rakes/tedders and for logistics operations with forklifts. It features excellent stability as well as high cut and chip resistance. PL 801 ensures an extended tire life-cycle.

UM

IS Standard

Construction

✦ Bias

Machinery

Agriculture ■ Rotor Rake/ Tedder, Industrial & Construction ■ Forklift



Version

STANDARD

Tire Type

TT

Tyre size

x8-9

LI/SS

Dimensions IS Standard

SW (IS) (mm)	200
OD (IS) (mm)	535
Rim Rec	6.00 E
Rim Alt	7.00 E

Load Capacity (IS)

km/h / bar	10:00:00																		
25 LOAD WHEEL	2755																		
25 STEER WHEEL	2120																		
10 OTHER VEHICLES	2755																		
25 OTHER VEHICLES	2120																		
STATIC SIDE LOADER	3200																		

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..