



MULTIMAX MP 525

Description

MULTIMAX MP 525 is an All-Steel multi-purpose radial tire designed for telehandlers, compact loaders, and graders in agro-industrial applications. The tire has been specifically developed to carry heavy loads at higher speeds both on and off the road. The large non-directional tread design provides exceptional traction on any surface. The strong sidewall ensures exceptional lateral stability, making it the ideal choice for agricultural and material handling operations.



UM

US Standard

Construction

 Radial

Machinery

Agriculture ▪ Universal Vehicle, Industrial & Construction ▪ Compact Loader

Version	STANDARD
Tire Type	TL
Tyre size	455/70R24
LI/SS	154;G

Dimensions US Standard

USA Code	94075195
OD (US) (in)	49.2
SLR (US) (in)	22.5
RC (US) (in)	149.4
Rim Rec	14
Rim Alt	13; DW14L
ECE	E11-54R-0021226

Load Capacity (US)

mph / psi	58	54
55	8270	-
30	-	8270
5	-	11400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..