



AW 711

Description

AW 711 is a radial implement tire specially designed for modern farming, and suitable for haulage, hay harvesting and soil tillage applications. Thanks to its special tread compound, AW 711 has an extended product life-cycle, whether it is used on soft or hard surfaces. The low rolling resistance during on-road travel ensures significant savings in fuel consumption. Thanks to the VF technology, AW 711 can carry heavy loads at low inflating pressure.



UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Hay Harvester

Version	STEEL BELTED
Tire Type	TL
Tyre size	VF410/50R16.5
LI/SS	153;B

Dimensions IS Standard

SW (IS) (mm)	410
OD (IS) (mm)	835
SLR (IS) (mm)	350
RC (IS) (mm)	2513
Rim Rec	AG 13.00
ECE	E11-106R-005024

Load Capacity (IS)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.6
From 10 to 50	1025	1345	1630	1890	2175	2465	2655	2910	3195	3650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..