



## EARTHMAX SR 459

### Description

EARTHMAX SR 459 is an All-Steel radial tire for rigid dump trucks operating in quarries and open pit mines. Its specifically developed symmetric design enables the fitting on both rear and front axles. Designed to ensure excellent durability, EARTHMAX SR 459 stands out for its extraordinarily high tread depth (the highest among all BKT tires in this size) combined with multi-ply steel belts providing superior protection against shocks and rock penetration.

### UM

IS Standard

### Construction

 Radial

### Machinery

OTR ■ Rigid Dump Truck



Version	HEAT RESISTANT COMPOUND
Tire Type	TL
Tyre size	27.00R49
LI/SS	223;B

## Dimensions IS Standard

OD (IS) (mm)	2720
SLR (IS) (mm)	1231
RC (IS) (mm)	8245
Rim Rec	19.50/4.0
TRA Code	E4

## Load Capacity (IS)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..