



## TRAC MASTER



### Description

TRAC MASTER is a soil tillage and lawn and garden tire, suitable for small tractors and implement machinery. Its tread design provides excellent field protection along with great traction in the fields and optimum self-cleaning properties.

### UM

US Standard

### Construction

 Bias

### Machinery

Agriculture ▪ Implement Machinery

Version STANDARD

Tire Type TL

Tyre size 300/60-12

LI/SS

## Dimensions US Standard

USA Code	94013166
SW (US) (in)	12.0
OD (US) (in)	25.4
SLR (US) (in)	11.2
RC (US) (in)	74.2
Rim Rec	10.5
Rim Alt	9.5
ECE	E11-106R-003597

## Load Capacity (US)

mph / psi	46
30	2270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..