



US standard



GROWING TOGETHER

MT 612



PRODUCT DATA SHEET



Bias



MT 612

MT 612 has been specially designed for multipurpose use on and off the road. Its strong casing allows carrying heavy loads at high speed whereas its broad lugs provide outstanding traction. The extra tread width ensures excellent flotation on sand and mud.

Performance



Durability



For muddy ground



Traction

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 20"	94029105	14.00 - 20	10	-	15.4	49.8	23.4	150.7	32	198	STD	18	TT	-
	94029433	14.00 - 20	10	-	15.4	49.8	23.4	150.7	32	203	STD	20	TT	-
	94036585	14.00 - 20	10	-	15.4	49.8	23.4	150.7	32	209	STD	22	TT	-
	94035922	16.0/70 - 20	13.00 T	-	15.9	43.1	20.5	131.0	32	136	STD	16	TT	-

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference