



EM 936 LOADER SPECIAL



Description

EM 936 LOADER SPECIAL has been specially designed for telehandlers in loading applications. It features outstanding riding comfort and enhanced self-cleaning properties. It also ensures a high level of handling comfort and provides excellent traction even under heavy-duty service conditions.

UM

IS Standard

Construction

◆ Bias

Machinery

Industrial & Construction ■ Telehandler

Version	STANDARD
Tire Type	TL
Tyre size	16.0/70-20
LI/SS	149;B

Dimensions IS Standard

OD (IS) (mm)	1090
SLR (IS) (mm)	480
RC (IS) (mm)	3295
Rim Rec	13 SDC
Rim Alt	13
TRA Code	E2

Load Capacity (IS)

km/h / bar	03:50:00														
50	3250														

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..