



US standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 34



PRODUCT DATA SHEET

EARTHMAX SR 34
R A D I A L O T R T I R E S



EARTHMAX SR 34 is an All Steel radial tyre specially engineered and designed for rigid dump trucks working in several operations like mining, quarry, logging and haulage. The non-directional block tread pattern provides excellent traction and stability on any type of terrain. EARTHMAX SR 34 is ideal for handling heavy loads. The strong All Steel casing features excellent wear and resistance to any snag and punctures. Its reinforced bead and the shoulder design contribute to an extended tire life-cycle even under the most heavy-duty service conditions.



Radial



Technologies



All Steel



Block Pattern



Heavy Duty



Reinforced Bead

Performance



Cut and Chip Resistance



Durability



Stability



Traction

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 25"	94070732	16.00 R 25	TL	**	177 B	CRC	E-3+	130	59.4	17.3	27.3	180.1	45	529	11.25/2.0	-
	94070749	16.00 R 25	TL	***	183 B	CRC	E-3+	130	59.4	17.3	27.3	180.1	45	529	11.25/2.0	-
	94076109	16.00 R 25	TL	***	183 B	UCRC	E-3+	-	59.4	17.3	27.3	180.1	45	529	11.25/2.0	-

CRC: Cut Resistant Compound - UCRC: Ultra Cut Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference