



## AW 705

### Description

AW 705 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. It is ideal for modern farming thanks to improved durability and high load capacity.

### UM

US Standard

### Construction

 Bias

### Machinery

Agriculture ■ Baler



Version	STUBBLE RESISTANT
Tire Type	TL
Tyre size	400/55-22.5
LI/SS	

## Dimensions US Standard

USA Code	94060306
SW (US) (in)	15.9
OD (US) (in)	40.0
SLR (US) (in)	17.4
RC (US) (in)	120.9
Rim Rec	AG 11.75
Rim Alt	12.25; AG 13.00

## Load Capacity (US)

mph / psi	73
5 FR	12345
15 FR	10495
20 FR	9875
25 FR	8820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..