



US standard



GROWING TOGETHER

# EM 938



PRODUCT DATA SHEET



Bias



140



# EM 938

EM 938 has been specially designed for excavators in road construction works. The tire is made of a special tread compound, which is particular resistant to cuts and snags, whilst the aggressive tread pattern provides excellent traction. EM 938 features outstanding self-cleaning properties. The strong casing provides extraordinary resistance to impacts and shocks even in heavy-duty operations.

**Performance**



Handling and Comfort



Heavy Duty



Self-Cleaning



Traction

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 20"	94046034	9.00 - 20	TT	14	-	STD	39.8	10.1	18.9	120.9	26	101	7.0	6.5 ; 7.5
	94064625	9.00 - 20	TT	16	-	STD	39.8	10.1	18.9	120.9	26	111	7.0	6.5 ; 7.5
	94071005	9.00 - 20 <b>NEWSIZE</b>	TT	18	-	STD	39.8	10.1	18.9	120.9	26	111	7.0	6.5 ; 7.5

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference