



US standard



GROWING TOGETHER

TR 128



PRODUCT DATA SHEET



Bias



TR 128

TR 128 has been specially designed for utility tractors and rototillers. The wide and deep lug design and the special cut-and-chip resistance compound provide an extended tire service life. TR 128 features maximum traction on wet soil.

Performance



Cut and Chip Resistance



High Load Capacity



Traction

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 12"	94044887	5 - 12	4 JA	-	5.0	21.8	10.3	66.9	30	14	STD	4	TT	-
	94055883	5 - 12	4 JA	-	5.0	21.8	10.3	66.9	30	14	STD	6	TT	60 A8
	94044894	6.00 - 12	4.00 E	4.00 E DT	6.3	25.0	11.7	75.8	32	22	STD	4	TT	65 A8
	94045242	6.00 - 12	4.00 E	4.00 E DT	6.3	25.0	11.7	75.8	32	22	STD	6	TT	72 A8
	94060511	6.00 - 12	4.00 E	4.00 E DT	6.3	25.0	11.7	75.8	32	22	STD	8	TT	78 A8
	94058129	180/85 D 12	5 JA	-	6.5	24.1	11.6	72.7	35	21	STD	4	TT	63 A6
	94059256	180/85 D 12	5 JA	-	6.5	24.1	11.3	72.7	35	21	STD	6	TT	72 A8
Ø 14"	94050345	7 - 14	5 JA	5 J	6.8	27.2	12.7	82.1	33	28	STD	8	TT	92 A8

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference