



US standard



GROWING TOGETHER

RIB 900



PRODUCT DATA SHEET



Bias



147

Performance



Durability



High Load Capacity



RIB 900

RIB 900 is suitable for transport, soil tillage and hay harvesting operations with trailers, implement machinery and balers. It offers great load capacity and a long tire life-cycle.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS	
			Rec.	Alt.										DW	FR
15.5"	94026357	400/60 - 15.5	AG 13.00	-	15.9	34.4	15.0	100.9	14	68	STD	10	TL	-	139A8
	94026173	400/60 - 15.5	AG 13.00	-	15.9	34.4	15.0	100.9	14	71	STD	14	TL	-	145A8
	94026340	400/60 - 15.5	AG 13.00	-	15.9	34.4	15.0	100.9	14	77	STD	16	TL	-	147A8

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling