

 | IS standard

BKT
GROWING TOGETHER

W 207



FICHE PRODUIT



Diagonal



W 207

W 207 est le pneu BKT ATV/VTT pour tous les applications sportives Tout Terrain. Grâce à la technologie M+S et le dessin particulier, il offre un maximum de traction dans n'importe quelles conditions. Ce pneu se distingue de par son excellente résistance aux perforations sur les terrains les plus difficiles.

Technologies



M+S

Performance



Sport



Traction

	DIMENSION	JANTE		S (mm)	D (mm)	R (mm)	C.d.R. (mm)	Version	PR	TT/TL	LI/SS
		Recommandée	Alternative								
Ø 8"	AT 22 X 11 - 8	9.0 AT	8.5 AT	272	561	-	-	STD	6	TL	-
Ø 9"	AT 22 X 11 - 9	9.0 AT	8.5 AT	272	561	-	-	STD	6	TL	-
	AT 25 X 12 - 9	9.5 AT	9.0 AT ; 10.0 AT	300	632	-	-	STD	6	TL	-
	AT 25 X 13 - 9	10.5 AT	10.0 AT	330	635	-	-	STD	6	TL	-
Ø 10"	AT 22 X 7 - 10	5.5 AT	6.0 AT	178	559	-	-	STD	6	TL	-
	AT 22 X 8 - 10	6.5 AT	6.0 AT	203	559	-	-	STD	6	TL	-
	AT 22 X 11 - 10	9.0 AT	8.5 AT	272	561	-	-	STD	6	TL	-
	AT 23 X 7 - 10	5.5 AT	6.0 AT	177	584	-	-	STD	6	TL	-
	AT 23 X 8 - 10	6.5 AT	6.0 AT	203	589	-	-	STD	6	TL	-
	AT 23 X 10 - 10	8.0 AT	7.5 AT ; 8.5 AT	249	587	-	-	STD	6	TL	-
	AT 24 X 11 - 10	9.0 AT	8.5 AT	279	610	-	-	STD	6	TL	-
	AT 25 X 11 - 10	9.0 AT	8.5 AT	285	640	-	-	STD	6	TL	-
	AT 25 X 12 - 10	9.5 AT	9.0 AT ; 10.0 AT	297	640	-	-	STD	6	TL	-

STD: Standard

Tolérances: D ± 2% - S ± 2% - R ± 2.5% - LI/SS: Indice de charge/Code de vitesse; S: Largeur de section; D: Diamètre extérieur; R: Rayon sans charge; C.d.R.: Circonférence de roulement



Diagonal

Technologies



M+S

Performance



Sport



Traction



	DIMENSION	JANTE		S (mm)	D (mm)	R (mm)	C.d.R. (mm)	Version	PR	TT/TL	LI/SS
		Recommandée	Alternative								
Ø 11"	AT 23 X 8 - 11	6.5 AT	6.0 AT	203	584	-	-	STD	6	TL	-
	AT 24 X 8 - 11	6.5 AT	6.0 AT	203	612	-	-	STD	6	TL	-
	AT 24 X 9 - 11	7.0 AT	7.5 AT	226	610	-	-	STD	6	TL	-
	AT 24 X 10 - 11	8.0 AT	7.5 AT ; 8.5 AT	249	612	-	-	STD	6	TL	-
	AT 25 X 8 - 11	6.5 AT	6.0 AT	203	638	-	-	STD	6	TL	-
	AT 25 X 10 - 11	8.0 AT	7.5 AT ; 8.5 AT	249	638	-	-	STD	6	TL	-
Ø 12"	AT 24 X 8 - 12	6.5 AT	6.0 AT	198	615	-	-	STD	6	TL	-
	AT 25 X 8 - 12	6.5 AT	6.0 AT	198	638	-	-	STD	6	TL	-
	AT 25 X 10 - 12	8.0 AT	6.5 AT ; 7.5 AT ; 8.5 AT	249	638	-	-	STD	6	TL	-
	AT 25 X 11 - 12	9.0 AT	8.5 AT	284	638	-	-	STD	6	TL	-
	AT 26 X 8 - 12	6.50 AT	6.00 AT	204	660	-	-	STD	6	TL	-
	AT 26 X 10 - 12	8.0 AT	7.5 AT ; 8.5 AT	241	658	-	-	STD	6	TL	-
	AT 26 X 12 - 12	9.5 AT	8.0 AT ; 8.5 AT ; 9.0 AT	299	658	-	-	STD	6	TL	-
	AT 27 X 10 - 12	8.0 AT	7.5 AT ; 8.5 AT	241	683	-	-	STD	6	TL	-

STD: Standard

Tolérances: D ± 2% - S ± 2% - R ± 2.5% - LI/SS: Indice de charge/Code de vitesse; S: Largeur de section; D: Diamètre extérieur; R: Rayon sans charge; C.d.R.: Circonférence de roulement



Diagonal

Technologies



M+S

Performance



Sport



Traction



	DIMENSION	JANTE		S (mm)	D (mm)	R (mm)	C.d.R. (mm)	Version	PR	TT/TL	LI/SS
		Recommandée	Alternative								
Ø 12"	AT 27 X 12 - 12	9.5 AT	8.5 AT ; 9.0 AT	299	683	-	-	STD	6	TL	-
	AT 28 X 10 - 12	8.0 AT	7.5 AT ; 8.5 AT	241	706	-	-	STD	6	TL	-
	AT 28 X 12 - 12	9.5 AT	8.5 AT ; 9.0 AT	299	706	-	-	STD	6	TL	-

STD: Standard



Tolérances: D ± 2% - S ± 2% - R ± 2.5% - LI/SS: Indice de charge/Code de vitesse; S: Largeur de section; D: Diamètre extérieur; R: Rayon sans charge; C.d.R.: Circonférence de roulement