



US standard



GROWING TOGETHER

TR 459



PRODUCT DATA SHEET



Bias



TR 459



TR 459 has been particularly designed for digging and loading operations as well as municipality and maintenance applications with tractors and backhoe loaders. It offers high stability and is available in two versions. The "special" version provides an extended tire life-cycle.

Performance



Stability



Traction

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	S.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 20"	94051700	400/70 - 20	TL	-	149A8	IND	42.9	15.9	-	-	33	125	13	12 SDC; 13 SDC; 14
Ø 24"	94016440	14.9 - 24	TL	8	137A8	IND	49.0	15.4	22.1	144.0	33	132	DW 13	DW 12; DW 11; DW 13 L
	94016457	14.9 - 24	TL	12	145A8	IND	49.0	15.4	22.1	144.0	33	139	DW 13	DW 12; DW 11; DW 13 L
	94016464	16.9 - 24	TL	8	142A8	IND	51.6	17.7	23.5	151.2	35	163	DW 15 L	DW 14 L
	94016488	16.9 - 24	TL	10	145A8	IND	51.6	17.7	23.2	151.6	35	165	DW 15 L	DW 14 L
	94016495	16.9 - 24	TL	12	149A8	IND	51.6	17.7	23.2	151.6	35	179	DW 15 L	DW 14 L
	94016563	17.5 L - 24	TL	8	139A8	IND	50.0	17.5	21.9	150.6	33	153	DW 15 L	DW 14 L
	94016587	17.5 L - 24	TL	10	144A8	IND	50.0	17.5	21.9	150.6	33	155	DW 15 L	DW 14 L
	94016594	17.5 L - 24	TL	12	148A8	IND	50.0	17.5	21.9	150.6	33	157	DW 15 L	DW 14 L
	94016617	18.4 - 24	TL	12	155A8	IND	54.1	18.6	24.0	162.0	36	211	DW 16 L	DW 15 L
	94016662	19.5 L - 24	TL	10	147A8	IND	52.5	19.3	23.0	158.7	35	200	DW 16 L	-
	94016686	19.5 L - 24	TL	12	151A8	IND	52.5	19.3	23.0	158.7	35	203	DW 16 L	-
	94035625	19.5 L - 24	TL	12	151A8	IND SPL	52.5	19.3	23.0	158.7	35	203	DW 16 L	-
94016709	21 L - 24	TL	12	155A8	IND	54.3	21.0	23.8	157.3	36	245	DW 18 L	-	
94054404	21 L - 24	TL	14	157A8	IND	54.3	21.0	23.8	157.3	36	250	DW 18 L	-	

IND: Industrial - IND SPL: Industrial Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Performance



Stability



Traction



	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	S.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 26"	94016624	18.4 - 26	TL	12	156 A8	IND	56.1	18.6	24.7	171.1	36	233	DW 16 L	DW 15 L
	94016631	18.4 - 26	TL	14	159 A8	IND	56.1	18.6	24.7	171.1	36	237	DW 16 L	DW 15 L
	94066223	18.4 - 26	TL	16	162 A8	IND	56.1	18.6	24.7	171.1	36	237	DW 16 L	DW 15 L
Ø 28"	94016525	16.9 - 28	TL	8	145 A8	IND	55.5	17.3	25.2	163.2	35	184	DW 15 L	DW 14 L
	94016532	16.9 - 28	TL	10	148 A8	IND	55.5	17.3	25.2	163.2	35	186	DW 15 L	DW 14 L
	94016556	16.9 - 28	TL	12	152 A8	IND	55.5	17.5	25.2	168.2	35	202	DW 15 L	DW 14 L
	94016648	18.4 - 28	TL	12	157 A8	IND	58.1	18.6	26.1	177.0	37	239	DW 16 L	DW 15 L
	94044337	21 L - 28	TL	12	157 A8	IND	58.3	21.1	-	-	36	278	DW 18 A	-
Ø 30"	94035595	16.9 - 30	TL	12	153 A8	IND	57.9	17.3	25.9	176.5	35	202	DW 15 L	DW 14 L

IND: Industrial



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference