



US standard



GROWING TOGETHER

LIFT STAR PLUS



PRODUCT DATA SHEET



Bias



LIFT STAR PLUS

LIFT STAR is a bias-ply tire specially designed for telehandlers operating in demanding construction operations and other severe applications. Its low-profile sidewall ensures excellent stability in high-lifting operations whereas its non-directional tread design allows for greater mounting versatility. In addition, the specially designed sidewall provides added cut-and-puncture protection.

Performance



Cut and Chip Resistance



Durability



Heavy Duty



Stability

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	S.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 28"	94053001	370/75 - 28	TL	14	-	STD	50.0	14.4	23.0	151.6	40	220	11.00	-
	94046225	400/75 - 28	TL	16	-	STD	51.9	15.7	23.3	155.3	40	242	12.00 GR	-

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference