



## SM 55 IND-5S

### Description

SM 55 IND-5S has been specially designed for reach stackers and container handlers. Its special abrasion-resistant tread compound provides an extended tire life on asphalt or concrete surfaces and offers excellent stability to vehicles in lift mode.

### UM

US Standard

### Construction

◆ Bias

### Machinery

Industrial & Construction ■ Container Handler



Version	PORT SPECIAL
Tire Type	TL
Tyre size	18.00-25
LI/SS	

## Dimensions US Standard

USA Code	94039609
OD (US) (in)	65.6
SLR (US) (in)	30.1
RC (US) (in)	201.5
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND5

## Load Capacity (US)

mph / psi	145
5	50625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..