



## AGRIMAX V-FLECTO

### Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.



### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ High-Power Tractor

Version	STANDARD
Tire Type	TL
Tyre size	VF650/65R38
LI/SS	169;D

## Dimensions IS Standard

SW (IS) (mm)	650
OD (IS) (mm)	1811
SLR (IS) (mm)	798
RC (IS) (mm)	5387
Rim Rec	DW 23 B
Rim Alt	DW 21 B
ECE	E11-106R-005022
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
70	2950	3480	3955	4430	4850	5275
from 65 to 40	3245	3825	4350	4870	5335	5800
30	3305	3900	4435	4965	5440	5915
20	3370	3975	4520	5060	5545	6030
10	3565	4205	4785	5355	5865	6380
*Upto 10 Cyc with front loader	4540	5355	6090	6815	7465	8120
10HT	3305	3900	4435	4965	5440	5915

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..