



IS standard



GROWING TOGETHER

# MULTIMAX

RADIAL MPT TIRES

## MP 519



PRODUCT DATA SHEET



Radial



Technologies



High Speed

Performance



Fuel Economy



Stability



# MULTIMAX MP 519

RADIAL MPT TIRES

🇬🇧 MULTIMAX MP 519 is a particularly suitable tire for light trucks in all transport applications. The steel-belted casing provides excellent stability at high-speed (90 km/h - 60 mph). Thanks to its low rolling resistance, the tire ensures reduced fuel consumption.

	Tire size	Type	PR	LI/SS	Version	S.W.	O.D.	SLR	RC	RIM	
						(mm)	(mm)	(mm)	(mm)	Rec.	Alt.
Ø 16"	7.50 R 16 LT	TL	6	109/ 107 G	STD	220	810	377	2449	6.00	5.50 F; 6 L; 7 L
	7.50 R 16 LT	TL	8	112/ 110 G	STD	220	810	377	2449	6.00	5.50 F; 6 L; 7 L

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference