



## EARTHMAX SR 31

### Description

EARTHMAX SR 31 is an All Steel radial tire specially designed for articulated dump trucks and wheel loaders. It provides extraordinary strength and stability, whilst the non-directional rigid block pattern stands for both excellent traction and maneuverability even on muddy ground. EARTHMAX SR 31 also features a special tread compound which is particularly cut-and-heat resistant. The radial casing structure also provides reduced rolling resistance offering significant fuel savings.



### UM

US Standard

### Construction

 Radial

### Machinery

Industrial & Construction ■ Loader,OTR ■ Articulated Dump Truck

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	29.5R25
LI/SS	200;B

## Dimensions US Standard

USA Code	94053742
OD (US) (in)	73.3
SLR (US) (in)	32.2
RC (US) (in)	218.7
Rim Rec	25.00/3.5
TRA Code	E3/L3

## Load Capacity (US)

mph / psi	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900
5	34200	35300	37500	38600	39700	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..