



IS standard



GROWING TOGETHER

MULTIMAX

RADIAL MPT TIRES

SR 261



PRODUCT DATA SHEET



Radial



150



MULTIMAX SR 261

RADIAL MPT TIRES

MULTIMAX SR 261 is an All Steel radial tire with multi-layer steel belts specially designed for Low Platform Trailer, Agri Trailer and Mobile Harbour Crane in transport applications and port operations. Its strong carcass and special tread compound ensure longer tire life. Thanks to its siped tread design, MULTIMAX SR 261 allows for superior traction in all applications. In addition, the unique 5 RIB tread design maximizes ground contact for even tread wear.

Technologies



All Steel



Strong Casing

Performance



Durability



Traction

	Tire size	Type	STAR RATING	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 17.5"	215/75 R 17.5	TL	-	135/133 J	STD	210	775	356	2371	6.00	6.75
Ø 19.5"	285/70 R 19.5	TL	-	150/148 J	STD	280	903	412	2779	8.25	7.50 ; 9.00

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference